Announcing...



The **אח**ס The **ודו**

We are pleased to announce the introduction of the אָאָרָיד וצפ. This model will replace the popular base models אָאָרָ דו וצ, אָאָרָ דו וצB, אָאָרָ דו וצR, and the אָאָרָ דו וצBR.

The **Dftx-iT I2e** features an updated design but preserves the spirit of simplicity and the size of the original base model units.

Since the Bump buttons are now standard on the **Dfix** -iT IZe the B option is no longer necessary, likewise since the faders are now protected by integral side walls so the **R** option is no longer necessary, operational access is better and the protection is superior.

FEATURES

Basic model for the ultimate in simplicity of operation.

The same dimensions and light weight allow hand held operation as with the earlier models.



Don't let the name -12 worry you, the full 512 channels of starting address are available by setting a DIP switch on the rear panel.

Fast to operate, fast frame rates for LED lighting.





Dimensions W, H, D Front / Rear: 3.8", 7.8", 1.6/2.3" (10, 120, 4 / 5.8 cm) Weight: 1.1lbs (0.5kg), shipping wt 2.2lbs (1kg) Model Number: 750-0813 Rechargeable internal Li-ion battery featuring days of operation on a single charge. Charging status LED, Low battery status LED.

Simultaneous charging and operation from either the ultra small AC adapter (included) or a Micro USB B cable connected to a portable power bank or any USB power source.

VESA mount threads provided on the bottom allow optional creative mounting using a huge variety of off the shelf mounting hardware: mic stands, monitor mounts, etc.

