## Integrated Controls, Inc.

## Announcing...



## The DMX-IT 5I2e

We are happy to announce the introduction of the DmX-iT SIZe.

This model will replace the venerable אחל-iד SI2 & the אחל-iד SI2R.

The **Dftx-it Size** features an updated design but preserves the spirit of simplicity and the size of the original units.

## **FEATURES**

 $\ensuremath{\mathsf{Memory}}$  – a full scene of level memory at an independent address and with its own Scene Master.

Fast to operate, fast frame rates for LED lighting.

A new Address mismatch LED indicates when the address setting does not match the current live address.

A feature to clear the entire DMX 512 universe has been added.

The faders are now protected by integral side walls so the  ${\bf R}$  option is no longer necessary, operational access is better and the protection is superior.



The same dimensions and light weight allow hand held operation as with the earlier models.





Dimensions W, H, D Front / Rear: 3.8", 7.8", 1.6/2.3" (10, 120, 4 / 5.8 cm) Weight: 1.1lbs (0.5kg), shipping wt 2.2lbs (1kg) Model Number: 750-0814 Rechargeable internal Li-ion battery featuring days of operation on a single charge. Charging status LED, Low battery status LED.

Simultaneous charging and operation from either the ultra small AC adapter (included) or a Micro USB B cable connected to a portable power bank or any USB power source.

VESA mount threads provided on the bottom allow optional creative mounting using a huge variety of off the shelf mounting hardware: mic stands, monitor mounts, etc.

